

# Maxen Henley 250L Wood Fireplace

Building Products Information Register Declaration



MAXEN

## PRODUCT

<b>Designated Building Product</b>	Class 1	<b>Manufacture Location</b>	Overseas
<b>Name</b>	Maxen Henley 250L Wood Fireplace	<b>Legal and Trading Name of Manufacturer</b>	On Behalf of Escea Ltd
<b>Line</b>	Maxen Wood Fires	<b>Legal and trading name of Importer</b>	Escea Ltd
<b>Identifier</b>	Maxen Henley 250L Wood Fireplace	<b>Importer Address for Service</b>	17 Carnforth St, Dunedin 9018
		<b>Importer Website</b>	<a href="https://www.escea.com/nz/">https://www.escea.com/nz/</a>
		<b>Importer Email</b>	info@escea.com
		<b>Importer Phone Number</b>	(03) 478 8220
		<b>Manufacturer NZBN</b>	9429036562480

## DECLARATION

Escea Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations. 2022.

## PRODUCT DESCRIPTION

The Maxen Henley 250L, is a free-standing, slow combustion, solid fuel fireplace intended for indoor use. This freestanding wood burning fireplace contains a glass fronted mild steel firebox with a 28.9L Firebox capacity, and a steel surround which provides radiant heat. Suitable for heating rooms up to 160m<sup>2</sup> in volume. The flue system comprises a single painted internal flue, with two additional liners as it passes through a roof. Damper control for the supply of air to the firebox, during operation and refueling, is fixed to exterior of the Fireplace.

The Maxen Henley 250L is intended for clean air installations where compliance with NES Air Quality standards is required. A rural conversion can be made to this fireplace for use outside of clean-air locations. Tested to *NZS 4012* with an efficiency of 65.4%, and tested to *NZS 4013* for emissions of 0.84g/kg. Tested to *AS/NZS 2918. 2001/2018 Appendix B* and *Appendix F*, for clearance to combustibles.

In rural areas, the Maxen Henley 250L can be used for hot water heating with a water booster system.

## SCOPE OF USE

The Maxen Henley 250L is intended to be used within residential dwellings, and small commercial premises. It is capable of heating up to 160m<sup>2</sup> in floor area (subject to specific building design). Ideally such spaces should be open plan areas, to maximise the free flow of air throughout.

This fireplace is intended to be installed onto a hearth. Minimum hearth dimensions should be in accordance with the manufacturer's instructions.

The flue pathway should be located directly above the fireplace, with minimal offsets to ensure adequate flue draw. Flue diameter internally is 150mm.

The Maxen Henley 250L is intended for clean air installations where compliance with NES Air Quality Standards may apply. A rural conversion can be made to this fireplace for use outside of clean-air locations.

## CONDITIONS OF USE

The Maxen Henley 250L must be installed to *AS/NZS 2918* and the manufacturer's instructions. These instructions are supplied with the fireplace and can be downloaded from the Maxen Website: <https://maxenfireplaces.com/>

This fireplace must be operated with a Maxen flue kit and components.

The product should be installed by an experienced wood fireplace installer or a member of NZ Home Heating Association.

## SUPPORTING DOCUMENTATION

The following additional documentation supports this declaration.

<b>Maxen Freestanding Wood Fire Owners Manual and Installation Instructions</b> (Design, Installation, Maintenance, Warranty)	630685_1	<a href="https://eps4kvbjsh.m.exactdn.com/wp-content/uploads/2023/10/630685_1-Maxen-Freestander-Manual-and-Install-Instructions.pdf">https://eps4kvbjsh.m.exactdn.com/wp-content/uploads/2023/10/630685_1-Maxen-Freestander-Manual-and-Install-Instructions.pdf</a>
<b>Maxen Henley 250L Builders and Architect Information Sheet</b> (Design, Installation)	630694_1	<a href="https://eps4kvbjsh.m.exactdn.com/wp-content/uploads/2023/10/630694_1-Henley-250-Spec-Sheet.pdf">https://eps4kvbjsh.m.exactdn.com/wp-content/uploads/2023/10/630694_1-Henley-250-Spec-Sheet.pdf</a>

# Maxen Henley 250L Wood Fireplace

Building Products Information Register Declaration



## RELEVANT BUILDING CODE CLAUSES

**B2 Durability** - B2.3.1 (b)

**C2 Prevention of Fire Occurring** - C2.2, C2.3

**F2 Hazardous Building Materials** - F2.3.1

**G4 Ventilation** - G4.3.3 (i), G4.3.5

**G12 Water** - G12.3.2, G12.3.6

## CONTRIBUTIONS TO COMPLIANCE

B2 Durability

Maxen Henley 250L complies with *B2.3.1 (B)* having a durability of 15 years when installed and operated in accordance with the manufacturer's instructions, and not exposed to moisture. Regular maintenance as indicated within the manufacturer's instructions, will allow for failure to be detected for hidden components, such as flue systems.

C2 Prevention of Fire Occurring

Maxen Henley 250L has been tested to, and complies with *AS/NZS2918, Appendix B and F*. Installation following the manufacturer's instructions, will ensure compliance with *Acceptable Solution C/AS1*, for clearances to combustible materials.

F2 Hazardous Building Materials

The Maxen Henley 250L Wood Fireplace is inert and safe when handled. The fireplace must be installed with a flue system fixed and operational. There are no requirements for this product to comply with *Acceptable Solution F2/AS1*.

G4 Ventilation

The Maxen Henley 250L Wood Fireplace must be installed with a flue system fixed and operational, and the fireplace operated with the door closed. This ensures that products of combustion are removed from a building and conforming to *NZBC Clause G4.3.3 (i)*.  
The Maxen Henley 250L Wood Fireplace requires room air for combustion. Additional ventilation of the building is required to compensate for combustion air removal. This is provided by windows or other openings with a net openable area of 5% of the floor area of the space, to conform with *Acceptable Solution G4/AS1 Sec. 1.3.2*.

G12 Water

Maxen Henley 250L allows for the use of a water booster or wetback system, to heat water from the fireplace. The water booster kit is supplied as secondary part and is to be installed in accordance with *NZBC G12 AS1* or *AS/NZ S3500.1*. The water booster kit uses 25mm copper pipework and compatible fittings to allow connection to the building's hot water supply network and low pressure hot water storage cylinder. A back-flow preventer to comply with *NZBC G12.3.2*, must be installed to avoid cross contamination of potable water, and a tempering valve to comply with *NZBC G12.3.6* must be incorporated into the system to reduce the likelihood of scalding.

## RESPONSIBLE PERSON

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Maxen Henley 250L Wood Fireplace is not subject to a warning or ban under s26 of the Building Act.

Signed for and on behalf of Escea Ltd:

**James Fisher**

Chief Innovation Officer - Escea Fireplace Company

M: 021 883 736 E: james@escea.com P: +64 3 478 8220

For Further information regarding this or any Maxen fireplace, please contact the Escea Architectural Advisory Team:  
Email: [aa@escea.com](mailto:aa@escea.com)

PH (NZ): 0800 17 3000

Installation Manual and CAD files are available via the QR Code or link:  
<https://maxenfireplaces.com/technical-downloads/>

